

RECOMMEND USING SEALIGUP HEAVY DUTY OR SEALIGUP PREMIUM HEAVY DUTY SEALANT

ALL OTR TIRES BY SIZE

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

10" & SMALLER RIMS

	3.50-6	11	
	4.00-6	13	
	3.50-8	12	
	4.00-8	15	
	5.70/5.00-8	21	
	4.00-9	17	
	6.90/6.00-9	28	
	6.50-10	34	
	7.50-10	41	
	9.00-10	49	

12" RIMS

	4.00-12	21	
	5.70-12	15	
	26 x 12.00-12	58	
	4.00-12	20	
	5.00-12	23	
	7.00-12	40	
	23 x 8.50-12	21	
	27 x 8.50-12	21	

14" RIMS

	5-14	24	
	11L-14	64	
	6.00-14	32	
	7.50-14	42	
	9.5L-14	55	
	8.5L-14	48	
	24 x 8.50-14	41	

15" RIMS

	4.00-15	22	
	5.00-15	25	
	5.70-15	31	
	5.90-15	32	
	6.40-15	34	
	6.70-15	37	
	7.5L-15	47	
	7.50-15	56	
	7.60-15	44	
	8.25-15	63	
	9.5L-15	57	
	14.0/65-15	96	
	25 x 7.50-15	38	
	27 x 8.50-15	45	
	7.00L15(29 x 8.0-15)	47	
	7.00-15(30 x 8.0-15)	47	
	27 x 9.50-15	49	
	10.00-15	71	
	11.00-15	78	
	11L-15	70	

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

	12.5L-15	79	0.7
	31 x 13.50-15	86	0.7
	31 x 15.50-15	96	0.8
	35 x 12.50-15	90	0.8
	35 x 15-15	104	0.9
	250-15	64	0.5
	300-15	96	0.8

16" RIMS

	5.50-16	32	0.3
	6.00-16	37	0.3
	6.50-16	40	0.4
	7.50-16	52	0.5
	7.50/8.00-16	55	0.5
	9.00-16	62	0.5
	9.5-16	63	0.5
	10.00-16	77	0.7
	11L-16	70	0.6
	11.00-16	95	0.8
	12.5L-16	82	0.7
	12.5/70-16	86	0.7
	12.4-16	91	0.8
	280/70-16	91	0.8

16.1" RIMS

	13.50-16.1	110	0.9
	14.5/75-16.1	107	0.9
	14L-16.1	109	0.9
	16.5L-16.1	134	1.1
	18.4-16.1	165	1.3
	19.5L-16.1	174	1.4
	21.5L-16.1	190	1.5
	19L-16.1	154	1.3
	38 x 20.00-16.1	154	1.3

16.5" RIMS

	10-16.5	72	0.6
	12-16.5	86	0.7

17.5" RIMS

	14-17.5	103	0.9
	36 x 16-17.5	117	1.0

18" RIMS

	7.50-18	102	0.8
	9.5-18	68	0.6
	10.5/80-18	75	0.6
	12.0/12.5-18	86	0.7
	4.00-18	24	0.2
	7.50-18	56	0.5
	12.5/65-18	86	0.7
	12.5/80-18	92	0.8
	15.0/55-18	91	0.8
	15.5/60-18	114	0.9

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.

RECOMMEND USING SEALIGUP HEAVY DUTY OR SEALIGUP PREMIUM HEAVY DUTY SEALANT

ALL OTR TIRES BY SIZE

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
	15.5/70-18	129	1.1
280/70-18		103	0.9

19" RIMS

	4.00-19	25	0.2
	6.00-19	43	0.3

19.5" RIMS

	15.00-19.5	132	1.0
	18.00-19.5	156	1.2
	40 x 19-19.5	144	1.1

20" RIMS

	7.50-20	57	0.5
	8.3-20	65	0.6
	8.50-20	81	0.7
	9.00-20	85	0.7
	9.50-20	70	0.6
	10.00-20	94	0.8
	11.00-20	103	0.9
	12.00-20	112	0.9
	10/10.5-20	85	0.7
	11.25-20	91	0.8
	12.5-20	102	0.8
	14.00-20	157	1.3
	16.00-20	194	1.6
	42 x 25.00-20	215	1.7
	44 x 18.00-20	237	1.9
	48 x 25.00-20	255	2.0
	48 x 31.00-20	312	2.5
	17.5/65-20	155	1.3
275/80-20		82	0.7
335/80-20		103	0.9
365/80-20		118	1.0
375/75-20		94	0.8
280/70-20		115	0.9
300/70-20		124	1.0
360/70-20		155	1.3
405/70-20		136	1.1

21" RIMS

	12-21	129	1.1
	14-21	170	1.4
	24-21	258	2.1

22" RIMS

	8.3-22	62	0.5
	7.50-22	63	0.5
	9.5-22	75	0.6

22.5" RIMS

	13-22.5	106	0.9
	15-22.5	131	1.1
	18-22.5	168	1.4

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
600/55-22.5		236	1.9
700/50-22.5		274	2.2
600/55-22.5		236	1.9
375/65-22.5		139	1.1

24" RIMS

	7.50-24	69	0.6
	9.00-24	70	0.6
	9.50-24	79	0.7
	11.00-24	122	1.0
	11.25-24	121	1.0
	12.00-24	122	1.0
	13.00-24	142	1.2
	14.00-24	171	1.4
	16.00-24	204	1.6
	8.3-24	65	0.6
	11.2-24	96	0.8
	12.4-24	114	0.9
	13.6-24	130	1.1
	14.9-24	147	1.2
	16.9-24	183	1.5
	17.5L-24	172	1.4
	18.4-24	200	1.6
	19.5L-24	200	1.6
	21L-24	228	1.8
	48 x 20.00-24	232	1.9
280/85-24		96	0.8
320/85-24		112	0.9
320/70-24		109	0.9
340/85-24		128	1.0
360/70-24		129	1.1
380/85-24		147	1.2
380/70-24		141	1.2
385/95-24		166	1.3
420/70-24		163	1.3
420/85-24		176	1.4
480/65-24		186	1.5
540/65-24		216	1.7

24.5" RIMS

	11.00-24.5	122	1.0
--	------------	-----	-----

25" RIMS

	15.5-25	158	1.3
	16.00-25	203	1.6
445/80-25	17.5-25	193	1.6
	18.00-25	270	2.2
525/80-25	20.5-25	253	2.0
	21.00-25	303	2.4
	23.5-25	310	2.5
	26.5-25	380	3.0

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.

RECOMMEND USING SEALIGUP HEAVY DUTY OR SEALIGUP PREMIUM HEAVY DUTY SEALANT**ALL OTR TIRES BY SIZE**

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

25" RIMS (con't)

	29.5-25	475	3.8
	54 x 37.00-25	417	3.3
	66 x 43.00-25	550	4.3
	66 x 44.00-25	590	4.7
	67 x 34.00-25	467	3.7
	66 x 43.00-25	563	4.4
	1050/50-25	556	4.4
	25/65-25	293	2.3
385/95-25		166	1.3
445/80-25		183	1.5
445/95-25		198	1.6
	54 x 31.00-25	341	2.7
650/65-25		300	2.4

26" RIMS

	14.9-26	156	1.3
420/85-26	16.9-26	190	1.5
	18.4-26	210	1.7
	23.1-26	294	2.3
	24L-26	279	2.2
	28L-26	363	2.9
	54 x 31.00-26	332	2.6
	57 x 31.00-26	350	2.8
	66 x 43.00-26	563	4.4
	67 x 34.00-26	467	3.7

26.5" RIMS

	600/55B26.5	250	2.0
	700/50B26.5	292	2.3

28" RIMS

	11.2-28	102	0.8
	12.4-28	120	1.0
	11.25-28	131	1.1
340/85-28	13.6-28	141	1.2
380/85-28	14.9-28	166	1.3
420/85-28	16.9-28	200	1.6
	18.4-28	214	1.7
	21L-28	244	2.0
320/85-28		123	1.0
340/85-28		143	1.2
420/70-28		176	1.4
480/65-28		201	1.6
540/65-28		232	1.9

29" RIMS

	24.00-29	416	3.3
	26.5-29	388	3.1
	29.5-29	465	3.7
	33.25-29	558	4.4
	65/30-29	451	3.6

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

	775/65-29	418	3.3
	875/65-29	492	3.9

30" RIMS

	7.2-30	171	1.4
	12.4-30	137	1.1
380/85-30	14.9-30	171	1.4
420/90-30	16.9-30	208	1.7
460/85-30	18.4-30	228	1.8
	23.1-30	310	2.5
420/85-30		301	2.4
540/65-30		240	1.9

32" RIMS

	9.5-32	97	0.8
	24.5-32	351	2.8
	30.5L-32	452	3.6
	35.5L-32	563	4.4
	68 x 50.00-32	690	5.4
	76 x 50.00-32	764	6.0
	76 x 50.00B32	764	6.0
	78 x 45.00-32	721	5.7
	DH 35.5L-32	574	4.5
	DH73 x 44.00-32	625	4.9
	VA35.5L-32	570	4.5
	VA73 x 44.00-32	640	5.0
	68 x 50.00-32	690	5.4
900/60-32		518	4.1

33" RIMS

	18.00-33	293	2.3
	33.5-33	610	4.8
	37.5-33	726	5.7
	21/90-33	366	2.9
	35/65-33	577	4.6
	65/35-33	560	4.4

34" RIMS

290/95-34		131	1.1
320/85-34		138	1.1
380/85-34	14.9-34	185	1.5
460/85-34	18.4-34	238	1.9
480/85-34	18.4-34	253	2.0
520/85-34	20.8-34	290	2.3
460/85-34		376	3.0
385/85-34		185	1.5
420/85-34		344	2.7
480/70-34		346	2.8
	23.1-34	341	2.7
600/65B34		306	2.4
700/55B34		355	2.8

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.

RECOMMEND USING SEALIGUP HEAVY DUTY OR SEALIGUP PREMIUM HEAVY DUTY SEALANT

ALL OTR TIRES BY SIZE

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

TIRE SIZE (Metric)	TIRE SIZE (Conventional)	Tire Sealant required (ozs)	Tire Sealant (Gals)
--------------------	--------------------------	-----------------------------	---------------------

35" RIMS

	21.00-35	375	3.0
	29.5-35	509	4.0
	33.25-35	589	4.7
	37.25-35	718	5.7

36" RIMS

	13.6-36	160	1.3
--	---------	-----	-----

38" RIMS

	11.2-38	128	1.0
	12.4-38	148	1.2
	14.9-38	193	1.6
	15.5-38	196	1.6
	16.9-38	229	1.8
480/80-38	18.4-38	267	2.1
520/85-38	20.8-38	318	2.5
320/85-38		150	1.2
540/65-38		273	2.2
600/65-38		328	2.6
650/65-38		377	3.0
420/85-38		389	3.1
460/85-38		424	3.4
480/70-38		392	3.1
650/85-38		424	3.4
710/70-38		524	4.1
800/70-38		513	4.1

39" RIMS

	37.5-39	770	6.1
	40.5/75-39	803	6.3
	40/65-39	767	6.0
	41.25/70-39	808	6.4
	45/65-39	860	6.8
	65/40-39	733	5.8

42" RIMS

	12.4-42	147	1.2
480/80-42	18.4-42	280	2.2
520/85-42	20.8-42	336	2.7
320/90-42		162	1.3
900/50-42		530	4.2
710/70-42		585	4.6

45" RIMS

	45/65-45	970	7.6
	65/45-45	932	7.3

46" RIMS

320/90-46	12.4-46	172	1.4
	14.9-46	216	1.7
480/80-46	18.4-46	293	2.3
320/90-46		172	1.4
380/90-46		221	1.8
420/80-46		239	1.9
520/85-46		338	2.7

48" RIMS

230/95-48		118	1.0
-----------	--	-----	-----

49" RIMS

	18.00-49	354	2.8
	27.00-49	615	4.9
	31/90-49	646	5.1

50" RIMS

380/90-50		229	1.8
320/90-50		182	1.5
380/105-50		259	2.1
480/80-50		308	2.5

51" RIMS

	30.00-51	754	5.9
	33.00-51	864	6.8
	36.00-51	992	7.8
	50/65-51	1200	9.4

54" RIMS

270/95-54		194	1.6
380/90-54		243	1.9

56.5" RIMS

	30-56.5	616	4.9
--	---------	-----	-----

57" RIMS

	37.00-57	1097	8.6
	40.00-57	1245	9.8
	49.5-57	1447	11.4
	46/90-57	1263	9.9
	49.5/85-57	1550	12.2
	50/80-57	1474	11.6
	50/90-57	1522	11.9
	53.5/85-57	1653	13.0
	55.5/80-57	1620	12.7
	58/85-57	1731	13.6
	65/65-57	1900	14.9
	70/70-57	2181	17.1

63" RIMS

	53/80-63	1796	14.1
	55/80-63	2002	15.7
	59/80-63	2134	16.7

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.