

**RECOMMEND USING ANY OF THE SEALIGUP HEAVY DUTY TIRE SEALANTS
(502,603,603R, 605R)**

CONSTRUCTION & MINING OTR TIRES BY SIZE

Tire Size	Tire Sealant required (ML)	Tire Sealant (L)	Tire Size	Tire Sealant required (ML)	Tire Sealant (L)
15" RIMS			33" RIMS		
7.50-15	1630	1.7	18.00-33	8660	8.7
14.0/65-15	2820	2.9	33.5-33	18020	18.1
35 x 15-15	3060	3.1	37.5-33	21460	21.5
16" RIMS			21/90-33	10810	10.9
12.5/70-16	2530	2.6	35/65-33	17060	17.1
18" RIMS			65/35-33	16560	16.6
12.5/65-18	2540	2.6	35" RIMS		
15.5/60-18	3350	3.4	21.00-35	11070	11.1
15.5/70-18	3790	3.8	29.5-35	15050	15.1
20" RIMS			33.25-35	17400	17.4
9.00-20	2510	2.6	37.25-35	21230	21.3
10.00-20	2760	2.8	39" RIMS		
11.00-20	3030	3.1	37.5-39	22760	22.8
12.00-20	3290	3.3	40.5/75-39	23750	23.8
16.00-20	5730	5.8	40/65-39	22660	22.7
17.5/65-20	4570	4.6	41.25/70-39	23880	23.9
335/80-20	3050	3.1	45/65-39	25410	25.5
365/80-20	3470	3.5	65/40-39	21670	21.7
405/70-20	4000	4.0	45" RIMS		
21" RIMS			45/65-45	28680	28.7
24-21	7620	7.7	65/45-45	27560	27.6
24" RIMS			49" RIMS		
12.00-24	3590	3.6	18.00-49	10460	10.5
13.00-24	4180	4.2	27.00-49	18170	18.2
14.00-24	5040	5.1	31/90-49	19080	19.1
16.00-24	6010	6.1	51" RIMS		
385/95-24	4900	4.9	30.00-51	22300	22.3
25" RIMS			33.00-51	25530	25.6
15.5-25	4680	4.7	36.00-51	29320	29.4
16.00-25	5990	6.0	50/65-51	35470	35.5
17.5-25	5710	5.8	56.5" RIMS		
18.00-25	7970	8.0	30-56.5	18200	18.2
20.5-25	7460	7.5	57" RIMS		
21.00-25	8940	9.0	37.00-57	32430	32.5
23.5-25	9150	9.2	40.00-57	36820	36.9
26.5-25	11230	11.3	49.5-57	42770	42.8
29.5-25	14040	14.1	46/90-57	37350	37.4
25/65-25	8660	8.7	49.5/85-57	45840	45.9
385/95-25	4900	4.9	50/80-57	43580	43.6
445/80-25	5400	5.4	50/90-57	44990	45.0
445/95-25	5830	5.9	53.5/85-57	48870	48.9
650/65-25	8850	8.9	55.5/80-57	47910	48.0
29" RIMS			58/85-57	51180	51.2
29.5-29	13730	13.8	65/65-57	56170	56.2
33.25-29	16510	16.6	70/70-57	64490	64.5
775/65-29	12360	12.4	63" RIMS		
875/65-29	14550	14.6	53/80-63	53110	53.2

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE
DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**

CONSTRUCTION & MINING OTR TIRES BY SIZE

Tire Size	Tire Sealant required (ML)	Tire Sealant (L)	Tire Size	Tire Sealant required (ML)	Tire Sealant (L)
			55/80-63	59210	59.3
			59/80-63	63100	63.1

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.



**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE
DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**

**FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE
DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.**