

RECOMMEND USING SEALITUP HI SPEED (605) SEALANT

MOTORCYCLE & SCOOTER TIRES

TIRE SIZE	Tire Sealant required (Ozs)
-----------	-----------------------------

6" Rims

130/90-6	6
145/70-6	7
5.4-6	8

8" Rims

70/100-8	3
3.00-8	4
3.50-8	5
4.00-8	6

10" Rims

80/100-10	4
90/100-10	5
80/90-10	4
90/90-10	5
100/90-10	6
110/90-10	6
120/90-10	7
130/90-10	8
90/80-10	5
110/80-10	6
120/80-10	7
2.50-10	4
2.75-10	4
3.00-10	5
3.50-10	6
4.00-10	7
5.4-10	10
6.7-10	13

12" Rims

80/100-12	5
110/100-12	7
90/90-12	5
100/90-12	6
110/90-12	7
120/80-12	8
130/70-12	8
2.75-12	5
3.00-12	5
4.00-12	7
4.50-12	9
6.7-12	14

17" Rims (con't)

160/55-17	12
170/55-17	13
180/55-17	14
180/50-17	14
190/50-17	14
2.00-17	5
2.25-17	5
2.50-17	6
2.75-17	6
3.00-17	7
3.25-17	7
3.50-17	8
4.50-17	10
4.60-17	11

TIRE SIZE	Tire Sealant required (Ozs)
-----------	-----------------------------

14" Rims

90/100-14	6
90/90-14	6
180/80-14	14
2.25-14	4
2.50-14	5
2.75-14	6
3.00-14	6
3.60-14	8
5.4-14	14

15" Rims

130/90-15	10
140/90-15	11
150/90-15	12
140/80-15	11
150/80-15	11
160/80-15	13
170/80-15	14
140/70-15	10
2.50-15	5
2.75-15	5
U90-15	11
V90-15	12
V85-15	12

16" Rims

80/100-16	6
90/100-16	7
80/90-16	6
90/90-16	7
100/90-16	7
110/90-16	8
120/90-16	9
130/90-16	10
140/90-16	11
100/80-16	7
110/80-16	8
120/80-16	9
130/80-16	10
140/80-16	11
150/80-16	12
160/80-16	13
120/70-16	9

18" Rims (con't)

120/70-18	9
130/70-18	10
140/70-18	11
150/70-18	12
160/70-18	13
130/60-18	10
140/60-18	11
150/60-18	12
160/60-18	13
170/60-18	14
180/55-18	14
180/50-18	14
2.25-18	6
2.50-18	6

TIRE SIZE	Tire Sealant required (Ozs)
-----------	-----------------------------

130/70-16 10

180/70-16 14

2.00-16 4

2.25-16 5

2.50-16 6

2.75-16 6

3.00-16 7

3.50-16 8

4.60-16 12

T90-16 10

U90-16 11

R85-16 9

17" Rims

70/100-17	5
100/100-17	8
110/100-17	9
80/90-17	6
90/90-17	7
100/90-17	8
110/90-17	9
120/90-17	10
130/90-17	11
90/80-17	7
100/80-17	7
110/80-17	8
120/80-17	9
130/80-17	10
140/80-17	11
150/80-17	12
100/70-17	7
110/70-17	8
120/70-17	9
130/70-17	10
140/70-17	11
150/70-17	12
160/70-17	13
120/60-17	9
130/60-17	10
140/60-17	10
150/60-17	11
160/60-17	12
170/60-17	13

19" Rims

70/100-19	6
90/100-19	8
100/100-19	9
110/100-19	10
70/90-19	6
90/90-19	7
100/90-19	8
110/90-19	9
120/90-19	10
110/80-19	9
2.00-19	5
2.50-19	6
2.75-19	7
3.00-19	8

FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALITUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.

RECOMMEND USING SEALITUP HI SPEED (605) SEALANT

MOTORCYCLE & SCOOTER TIRES

TIRE SIZE	Tire Sealant required (Ozs)
5.00-17	12
5.10-17	12
S90-17	10
T90-17	11

18" Rims

90/100-18	7
100/100-18	8
110/100-18	9
120/100-18	10
90/90-18	7
100/90-18	8
110/90-18	9
120/90-18	10
130/90-18	11
4.25/85-18	10
100/80-18	8
110/80-18	9
120/80-18	10
130/80-18	11
140/80-18	12
150/80-18	13

TIRE SIZE	Tire Sealant required (Ozs)
2.75-18	7
3.00-18	7
3.25-18	8
3.50-18	9
3.60-18	9
4.00-18	10
4.10-18	11
4.25-18	11
4.50-18	12
4.60-18	10
5.10-18	14
J90-18	7
L90-18	8
M90-18	8
N90-18	9
P90-18	10
R90-18	10
P85-18	10
S85-18	10
T85-18	11
T80-18	11

TIRE SIZE	Tire Sealant required (Ozs)
3.25-19	8
3.50-19	9
3.60-19	10
4.10-19	11
J90-19	7
L90-19	8
M90-19	8

21" Rims

70/100-21	6
80/100-21	7
80/90-21	7
90/90-21	8
80/80-21	7
100/80-21	9
2.50-21	7
2.75-21	7
3.00-21	8
3.25-21	9
H90-21	7

23" Rims

3.00-23	9
---------	---

FOR USE IN TUBELESS TIRES WITH DELTA FIRST'S LINE OF SEALITUP TIRE SEALANTS. FOR TUBES CONSULT SPECIAL DOSAGE CHARTS. FOR OTHER TYPES OF TIRES, SEE SEPARATE APPLICATION CHARTS.