

USE SEALIGUP HEAVY DUTY OR PREMIUM HEAVY DUTY SEALANT ONLY

SKID STEER LOADER TIRES

TIRE SIZE	Tire Sealant required (ozs)	Tire Sealant (Gals)
5.70-12	30	0.3
27 x 8.50-15	53	0.5
27 x 10.50-15	64	0.5
31 x 15.50-15	112	0.9
10-16.5	72	0.6
12-16.5	86	0.7
14-17.5	103	0.9
15-19.5	132	1.1

FORESTRY TIRES

TIRE SIZE	Tire Sealant required (ozs)	Tire Sealant (Gals)
21.5L-16.1	190	1.5
67x34.00-25	467	3.7
18.4-26	210	1.7
23.1-26	294	2.3
28L-26	363	2.9
67x34.00-26	467	3.7
66x43.00-26	563	4.4
600/55B26.5	250	2.0
700/50B26.5	292	2.3
16.9-30	201	1.6
24.5-32	348	2.8

FORKLIFT TIRES

TIRE SIZE	Tire Sealant required (Ozs)	Tire Sealant (Gals)
5.70/5.00-8	21	0.2
18X7-8	28	0.3
6.00-9	27	0.3
6.90/6.00-9	28	0.3
6.50-10	34	0.3
7.50-10	44	0.4
7.00-12	40	0.4
7.00L15(29 x 8.0-15)	47	0.4
7.00-15(30 x 8.0-15)	47	0.4
7.00L15	48	0.4
7.50L15	59	0.5
8.15-15(28 x 9.0-15)	50	0.4
8.25-15	66	0.6
250-15	64	0.5
300-15	96	0.8

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.