

RECOMMEND USING SEALIGUP HI SPEED (605) SEALANT

TRAILER TIRES

BIAS PLY TRAILER TIRES - BLACK SIDEWALL

TIRE SIZE	Tire Sealant required (ML)
4.80-8	250
6.00-9	320
5.70-8	320
16.5 X 6.50-8	350
18.5 X 8.50-8	480
20.5 X 8.00-10	500
22.5 X 8.00-12	610
4.80-12	320
5.30-12	420

A78-13 ST	440
B78-13 ST	520
C78-13 ST	550
E78-14 ST	620
F65-14 ST	570
F78-14 ST	670
G78-14 ST	700
F65-15 ST	600
F78-15 ST	640
H78-15 ST	760

RADIAL SPECIAL TRAILER

ST175/80--13	290
ST205/75--14	430
ST215/75--14	490
ST205/75--15	430
ST225/75--15	530

LOW PLATFORM TRAILER TIRES

7.50-15	150
8.25-15	190
9.00-15	210
8.25R15TR G	960
9R17.5HC H	930
235/75R17.5 H	920
215/75R17.5 H	840
275/70R22.5 H	1210
11R17.5 G	1220

MOBILE HOME TIRES

TIRE SIZE	Tire Sealant required (ML)
7-14.5 MH	610
8-14.5 MH	700
9-14.5 MH	780

RV TIRES

TIRE SIZE	Tire Sealant required (ML)
19.5" RIMS	
225/70-19.5	850
245/70-19.5	950
245/70-19.5	950
22.5" RIMS	
295/75-22.5	1330
255/70-22.5	1070
275/70-22.5	1160
275/80-22.5	1320
315/80-22.5	1540
24.5" RIMS	
285/75-24.5	1370

FOR ANY TUBE TYPE TIRE, USE THE DOSAGE AMOUNT SHOWN BUT BE CERTAIN TO USE DELTA FIRST'S SPECIALLY DESIGNED SEALIGUP TUBE SEALANT.